

Pebble⁴

Technical data & specifications

Target markets:

- Identification
- Leisure
- Loyalty
- Education
- Transit
- ePayment



Pebble⁴ is designed to cater to all your requirements, be they small runs or bulk personalization of plastic cards.

It is the ideal solution for any type of application that requires single-sided printing of badges.

Thanks to the most advanced printing engine in the market, **Pebble⁴** delivers high-definition badges within seconds. This solution benefits from the latest encoding technologies: ISO or JIS2 magnetic tracks, and smart card with contact or contactless (RFID). These encoding options can be seamlessly combined to personalize multifeatured cards in a single pass.

Pebble⁴ comes with a very convenient 100-card feeder. Yet, it can also turn into an elegant over-the-counter display, thanks to the manual feeding option that lets you print your badges, card by card, for instant delivery to the holder.

Pebble⁴ comes in a splash of three different translucent colors that can be interchanged: switch from Fire Red to Jungle Green to Ocean Blue, and make sure **Pebble⁴** is always in line with your environment or taste.

The **Pebble⁴** range of printers proudly carries the stamp of Evolis' strong commitment to reliability, and therefore, benefits from unmatched quality along with a pioneering **3-year warranty**.

Standard Ship kit :

- Pebble⁴ printer
- Power supply
- Power cord
- USB cable
- eMedia Card designer
 - Incl. Excel database*
- XP, 2003 and Vista drivers
- Cleaning starter kit
- 3-Year warranty
- RoHS compliant

Main Characteristics

Single-sided color printing module
300 dpi print head (11.8 dots/mm)
USB port
16 MB RAM allowing two card storages (front & back)
Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil)
Output hopper with a capacity of 100 cards (0.76 mm - 30 mil)
1-Button and 4-LED control panel

Options & Accessories

Pebble⁴-CR79 for CR79 & CR80 cards (printing only, no encoding)
USB & Ethernet TCP-IP ports, internal USB Hub
Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil)
Manual card feeder for front-desk operation
Pebble Travel Bag
Pebble Travel Case

Encoding options

(Can be combined together)

Magnetic stripe encoder ISO 7811 HiCo/ LoCo or JIS2
Smart contact station - ISO 7816-2
Smart contact station and encoding unit - PC/SC, EMV 2000-1
Contactless encoding unit - ISO 14443A, B, ISO 15693, Mifare[®], DesFire[®], HID iCLASS[®], HID PROX[®]
Other types upon request

Print mode

Color dye sublimation and monochrome thermal transfer
Enhanced color management system for top quality pictures
Edge-to-edge printing
Integrated ribbon saver for monochrome printing
Integrated ½ Panel YMCKO picture management

Performance

Color 1 side (YMCKO): 150 cards/hour
Monochrome 1 side: up to 1000 cards/hour

Ribbons

2-panel KO black monochrome ribbon - 500 cards/roll
5-panel YMCKO color ribbon - 200 cards/roll
Half-panel YMCKO color ribbon - 400 cards/roll
Monochrome ribbons - up to 1000 cards/roll (black, red, green, blue, white, gold and silver)
Varnish hologram - 350 cards/roll
Scratch-Off - up to 1000 cards/roll

Supported platforms

Windows[™] XP, 2003 and Vista, 32 & 64 bits
Mac[™] OS X v10.2, 10.3 and 10.4 (free download)
Linux (free download)

Software supplied

eMedia Card Designer Software Standard Edition for designing and editing badges
Connection to Microsoft[™] Excel databases
Data Import & Export feature
Magnetic encoding
Unlimited version

Cards characteristics

Types	All PVC, Composite PVC cards, PET, ABS1 and varnished1 cards
Format	ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125") ISO CR-79 (52.10 mm x 83.90 mm - 3.303" x 2.051") as an option
Thickness	From 0.25 mm (10 mil) to 1 mm (40 mil)

Warranty

Printer, print head: 3-year warranty, unlimited number of passes, subject to observance of specific conditions and use of Evolis genuine consumables
Use Evolis Genuine products for best performance and extended lifespan of your printer

Weight & Size

Printer size	Height: 192 mm (7.55") - Length: 396 mm (15.59") - Width: 235 mm (9.25")
Printer weight	5.9 Kg (13 Lbs)

Electrical & Environmental

Electrical	Power supply: 110-230 Volts AC, 1.8 A, 60-50 Hertz - Printer: 24 Volts DC, 3 A
Environmental	Min/max operating temperature: 15° / 30° C (59° / 86° F) Humidity: 20% to 65% non-condensing Min/max storage temperature: -5° / +70° C (23° / 158° F) Storage humidity: 20% to 70% non-condensing Operating ventilation: free air

Miscellaneous

RoHS compliant